



Computer Fundamentals: Pradeep K. Sinha & Priti Sinha

Learning Objectives

In this chapter you will learn about:

- § Computer data
- § Computer codes: representation of data in binary
- § Most commonly used computer codes
- § Collating sequence

Ref. Page 36 Chapter 4: Computer Codes Slide 2/30

Computer Fundamentals: Pradeep K. Sinha & Priti Sinha

Data Types

- § **Numeric Data** consists of only numbers 0, 1, 2, ..., 9
- § **Alphabetic Data** consists of only the letters A, B, C, ..., Z, in both uppercase and lowercase, and blank character
- § **Alphanumeric Data** is a string of symbols where a symbol may be one of the letters A, B, C, ..., Z, in either uppercase or lowercase, or one of the digits 0, 1, 2, ..., 9, or a special character, such as + - * / , . () = etc.

Ref. Page 36 Chapter 4: Computer Codes Slide 3/30

Computer Fundamentals: Pradeep K. Sinha & Priit Sinha

Computer Codes

- § Computer codes are used for internal representation of data in computers
- § As computers use binary numbers for internal data representation, computer codes use binary coding schemes
- § In binary coding, every symbol that appears in the data is represented by a group of bits
- § The group of bits used to represent a symbol is called a byte

(Continued on next slide)

Ref. Page 36 Chapter 4: Computer Codes Slide 4/30

Computer Fundamentals: Pradeep K. Sinha & Priit Sinha

Computer Codes

(Continued from previous slide...)

- § As most modern coding schemes use 8 bits to represent a symbol, the term byte is often used to mean a group of 8 bits
- § Commonly used computer codes are BCD, EBCDIC, and ASCII

Ref. Page 36 Chapter 4: Computer Codes Slide 5/30

Computer Fundamentals: Pradeep K. Sinha & Priit Sinha

BCD

- § BCD stands for Binary Coded Decimal
- § It is one of the early computer codes
- § It uses 6 bits to represent a symbol
- § It can represent 64 (2^6) different characters

Ref. Page 36 Chapter 4: Computer Codes Slide 6/30

Coding of Alphabetic and Numeric Characters in BCD

Char	BCD Code		Octal
	Zone	Digit	
A	11	0001	61
B	11	0010	62
C	11	0011	63
D	11	0100	64
E	11	0101	65
F	11	0110	66
G	11	0111	67
H	11	1000	70
I	11	1001	71
J	10	0001	41
K	10	0010	42
L	10	0011	43
M	10	0100	44

Char	BCD Code		Octal
	Zone	Digit	
N	10	0101	45
O	10	0110	46
P	10	0111	47
Q	10	1000	50
R	10	1001	51
S	01	0010	22
T	01	0011	23
U	01	0100	24
V	01	0101	25
W	01	0110	26
X	01	0111	27
Y	01	1000	30
Z	01	1001	31

(Continued on next slide)

Ref. Page 37

Chapter 4: Computer Codes

Slide 7/30

Coding of Alphabetic and Numeric Characters in BCD

(Continued from previous slide..)

Character	BCD Code		Octal Equivalent
	Zone	Digit	
1	00	0001	01
2	00	0010	02
3	00	0011	03
4	00	0100	04
5	00	0101	05
6	00	0110	06
7	00	0111	07
8	00	1000	10
9	00	1001	11
0	00	1010	12

Ref. Page 37

Chapter 4: Computer Codes

Slide 8/30

[illegible]

BCD Coding Scheme (Example 1)

Example

Show the binary digits used to record the word BASE in BCD

Solution:

B = 110010 in BCD binary notation

A = 110001 in BCD binary notation

S = 010010 in BCD binary notation

E = 110101 in BCD binary notation

So the binary digits

110010 110001 010010 110101
B A S E

will record the word BASE in BCD

Ref. Page 38

Chapter 4: Computer Codes

Slide 9/30

[illegible]

Computer Fundamentals: Pradeep K. Sinha & Priit Sinha

BCD Coding Scheme (Example 2)

Example

Using octal notation, show BCD coding for the word DIGIT

Solution:

D = 64 in BCD octal notation
I = 71 in BCD octal notation
G = 67 in BCD octal notation
I = 71 in BCD octal notation
T = 23 in BCD octal notation

Hence, BCD coding for the word DIGIT in octal notation will be

64 71 67 71 23
D I G I T

Ref. Page 38Chapter 4: Computer CodesSlide 10/30

Computer Fundamentals: Pradeep K. Sinha & Priit Sinha

EBCDIC

§ EBCDIC stands for Extended Binary Coded Decimal Interchange Code

§ It uses 8 bits to represent a symbol

§ It can represent 256 (2⁸) different characters

Ref. Page 38Chapter 4: Computer CodesSlide 11/30

Computer Fundamentals: Pradeep K. Sinha & Priit Sinha

Coding of Alphabetic and Numeric Characters in EBCDIC

Char	EBCDIC Code		Hex
	Digit	Zone	
A	1100	0001	C1
B	1100	0010	C2
C	1100	0011	C3
D	1100	0100	C4
E	1100	0101	C5
F	1100	0110	C6
G	1100	0111	C7
H	1100	1000	C8
I	1100	1001	C9
J	1101	0001	D1
K	1101	0010	D2
L	1101	0011	D3
M	1101	0100	D4

Char	EBCDIC Code		Hex
	Digit	Zone	
N	1101	0101	D5
O	1101	0110	D6
P	1101	0111	D7
Q	1101	1000	D8
R	1101	1001	D9
S	1110	0010	E2
T	1110	0011	E3
U	1110	0100	E4
V	1110	0101	E5
W	1110	0110	E6
X	1110	0111	E7
Y	1110	1000	E8
Z	1110	1001	E9

(Continued on next slide)

Ref. Page 39Chapter 4: Computer CodesSlide 12/30

Computer Fundamentals: Pradeep K. Sinha & Priit Sinha

Coding of Alphabetic and Numeric Characters in EBCDIC

(Continued from previous slide...)

Character	EBCDIC Code		Hexadecimal Equivalent
	Digit	Zone	
0	1111	0000	F0
1	1111	0001	F1
2	1111	0010	F2
3	1111	0011	F3
4	1111	0100	F4
5	1111	0101	F5
6	1111	0110	F6
7	1111	0111	F7
8	1111	1000	F8
9	1111	1001	F9

Ref. Page 39 Chapter 4: Computer Codes Slide 13/30

Computer Fundamentals: Pradeep K. Sinha & Priit Sinha

Zoned Decimal Numbers

- § Zoned decimal numbers are used to represent numeric values (positive, negative, or unsigned) in EBCDIC
- § A sign indicator (C for plus, D for minus, and F for unsigned) is used in the zone position of the rightmost digit
- § Zones for all other digits remain as F, the zone value for numeric characters in EBCDIC
- § In zoned format, there is only one digit per byte

Ref. Page 39 Chapter 4: Computer Codes Slide 14/30

Computer Fundamentals: Pradeep K. Sinha & Priit Sinha

Examples Zoned Decimal Numbers

Numeric Value	EBCDIC	Sign Indicator
345	F3F4F5	F for unsigned
+345	F3F4C5	C for positive
-345	F3F4D5	D for negative

Ref. Page 40 Chapter 4: Computer Codes Slide 15/30

Computer Fundamentals: Pradeep K. Sinha & Priit Sinha

Packed Decimal Numbers

§ Packed decimal numbers are formed from zoned decimal numbers in the following manner:

Step 1: The zone half and the digit half of the rightmost byte are reversed

Step 2: All remaining zones are dropped out

§ Packed decimal format requires fewer number of bytes than zoned decimal format for representing a number

§ Numbers represented in packed decimal format can be used for arithmetic operations

Ref. Page 39
Chapter 4: Computer Codes
Slide 14/30

Computer Fundamentals: Pradeep K. Sinha & Priit Sinha

Examples of Conversion of Zoned Decimal Numbers to Packed Decimal Format

Numeric Value	EBCDIC	Sign Indicator
345	F3F4F5	345F
+345	F3F4C5	345C
-345	F3F4D5	345D
3456	F3F4F5F6	03456F

Ref. Page 40
Chapter 4: Computer Codes
Slide 17/30

Computer Fundamentals: Pradeep K. Sinha & Priit Sinha

EBCDIC Coding Scheme

Example

Using binary notation, write EBCDIC coding for the word BIT. How many bytes are required for this representation?

Solution:

B = 1100 0010 in EBCDIC binary notation
I = 1100 1001 in EBCDIC binary notation
T = 1110 0011 in EBCDIC binary notation

Hence, EBCDIC coding for the word BIT in binary notation will be

11000010 11001001 11100011
 B I T

3 bytes will be required for this representation because each letter requires 1 byte (or 8 bits)

Ref. Page 40
Chapter 4: Computer Codes
Slide 18/30

Computer Fundamentals: Pradeep K. Sinha & Priit Sinha

ASCII

§ ASCII stands for American Standard Code for Information Interchange.

§ ASCII is of two types – ASCII-7 and ASCII-8

§ ASCII-7 uses 7 bits to represent a symbol and can represent 128 (2^7) different characters

§ ASCII-8 uses 8 bits to represent a symbol and can represent 256 (2^8) different characters

§ First 128 characters in ASCII-7 and ASCII-8 are same

Ref. Page 40
Chapter 4: Computer Codes
Slide 19/30

Computer Fundamentals: Pradeep K. Sinha & Priit Sinha

Coding of Numeric and Alphabetic Characters in ASCII

Character	ASCII-7 / ASCII-8		Hexadecimal Equivalent
	Zone	Digit	
0	0011	0000	30
1	0011	0001	31
2	0011	0010	32
3	0011	0011	33
4	0011	0100	34
5	0011	0101	35
6	0011	0110	36
7	0011	0111	37
8	0011	1000	38
9	0011	1001	39

(Continued on next slide)

Ref. Page 42
Chapter 4: Computer Codes
Slide 20/30

Computer Fundamentals: Pradeep K. Sinha & Priit Sinha

Coding of Numeric and Alphabetic Characters in ASCII

(Continued from previous slide...)

Character	ASCII-7 / ASCII-8		Hexadecimal Equivalent
	Zone	Digit	
A	0100	0001	41
B	0100	0010	42
C	0100	0011	43
D	0100	0100	44
E	0100	0101	45
F	0100	0110	46
G	0100	0111	47
H	0100	1000	48
I	0100	1001	49
J	0100	1010	4A
K	0100	1011	4B
L	0100	1100	4C
M	0100	1101	4D

(Continued on next slide)

Ref. Page 42
Chapter 4: Computer Codes
Slide 21/30

Computer Fundamentals: Pradeep K. Sinha & Priit Sinha

Coding of Numeric and Alphabetic Characters in ASCII

(Continued from previous slide..)

Character	ASCII-7 / ASCII-8		Hexadecimal Equivalent
	Zone	Digit	
N	0100	1110	4E
O	0100	1111	4F
P	0101	0000	50
Q	0101	0001	51
R	0101	0010	52
S	0101	0011	53
T	0101	0100	54
U	0101	0101	55
V	0101	0110	56
W	0101	0111	57
X	0101	1000	58
Y	0101	1001	59
Z	0101	1010	5A

Ref. Page 42
Chapter 4: Computer Codes
Slide 22/30

Computer Fundamentals: Pradeep K. Sinha & Priit Sinha

ASCII-7 Coding Scheme

Example

Write binary coding for the word BOY in ASCII-7. How many bytes are required for this representation?

Solution:

B = 1000010 in ASCII-7 binary notation
O = 1001111 in ASCII-7 binary notation
Y = 1011001 in ASCII-7 binary notation

Hence, binary coding for the word BOY in ASCII-7 will be

1000010 1001111 1011001
B O Y

Since each character in ASCII-7 requires one byte for its representation and there are 3 characters in the word BOY, 3 bytes will be required for this representation

Ref. Page 43
Chapter 4: Computer Codes
Slide 23/30

Computer Fundamentals: Pradeep K. Sinha & Priit Sinha

ASCII-8 Coding Scheme

Example

Write binary coding for the word SKY in ASCII-8. How many bytes are required for this representation?

Solution:

S = 01010011 in ASCII-8 binary notation
K = 01001011 in ASCII-8 binary notation
Y = 01011001 in ASCII-8 binary notation

Hence, binary coding for the word SKY in ASCII-8 will be

01010011 01001011 01011001
S K Y

Since each character in ASCII-8 requires one byte for its representation and there are 3 characters in the word SKY, 3 bytes will be required for this representation

Ref. Page 43
Chapter 4: Computer Codes
Slide 24/30

Computer Fundamentals: Pradeep K. Sinha & Priit Sinha

Unicode

§ Why Unicode:

§ No single encoding system supports all languages

§ Different encoding systems conflict

§ Unicode features:

§ Provides a consistent way of encoding multilingual plain text

§ Defines codes for characters used in all major languages of the world

§ Defines codes for special characters, mathematical symbols, technical symbols, and diacritics

Ref. Page 44
Chapter 4: Computer Codes
Slide 25/30

Computer Fundamentals: Pradeep K. Sinha & Priit Sinha

Unicode

§ Unicode features (continued):

§ Capacity to encode as many as a million characters

§ Assigns each character a unique numeric value and name

§ Reserves a part of the code space for private use

§ Affords simplicity and consistency of ASCII, even corresponding characters have same code

§ Specifies an algorithm for the presentation of text with bi-directional behavior

§ Encoding Forms

§ UTF-8, UTF-16, UTF-32

Ref. Page 44
Chapter 4: Computer Codes
Slide 26/30

Computer Fundamentals: Pradeep K. Sinha & Priit Sinha

Collating Sequence

§ Collating sequence defines the assigned ordering among the characters used by a computer

§ Collating sequence may vary, depending on the type of computer code used by a particular computer

§ In most computers, collating sequences follow the following rules:

1. Letters are considered in alphabetic order (A < B < C ... < Z)

2. Digits are considered in numeric order (0 < 1 < 2 ... < 9)

Ref. Page 46
Chapter 4: Computer Codes
Slide 27/30

Computer Fundamentals: Pradeep K. Sinha & Priit Sinha

Sorting in EBCDIC

Example

Suppose a computer uses EBCDIC as its internal representation of characters. In which order will this computer sort the strings 23, A1, 1A?

Solution:

In EBCDIC, numeric characters are treated to be greater than alphabetic characters. Hence, in the said computer, numeric characters will be placed after alphabetic characters and the given string will be treated as:

$A1 < 1A < 23$

Therefore, the sorted sequence will be: A1, 1A, 23.

Ref. Page 46 Chapter 4: Computer Codes Slide 28/30

Computer Fundamentals: Pradeep K. Sinha & Priit Sinha

Sorting in ASCII

Example

Suppose a computer uses ASCII for its internal representation of characters. In which order will this computer sort the strings 23, A1, 1A, a2, 2a, aA, and Aa?

Solution:

In ASCII, numeric characters are treated to be less than alphabetic characters. Hence, in the said computer, numeric characters will be placed before alphabetic characters and the given string will be treated as:

$1A < 23 < 2a < A1 < Aa < a2 < aA$

Therefore, the sorted sequence will be: 1A, 23, 2a, A1, Aa, a2, and aA

Ref. Page 47 Chapter 4: Computer Codes Slide 29/30

Computer Fundamentals: Pradeep K. Sinha & Priit Sinha

Key Words/Phrases

- § Alphabetic data
- § Alphanumeric data
- § American Standard Code for Information Interchange (ASCII)
- § Binary Coded Decimal (BCD) code
- § Byte
- § Collating sequence
- § Computer codes
- § Control characters
- § Extended Binary-Coded Decimal Interchange Code (EBCDIC)
- § Hexadecimal equivalent
- § Numeric data
- § Octal equivalent
- § Packed decimal numbers
- § Unicode
- § Zoned decimal numbers

Ref. Page 47 Chapter 4: Computer Codes Slide 30/30
